

4 Channel Camera Kit



Specifications:

DVR Specifications

- Supports 4 Cameras
- 4 Video Inputs - RJ45 Connectors
- Composite Video Output and VGA output
- 4 Alarm Inputs / 1 Alarm Output
- MPEG-4 Compression
- Cameras are Powered from DVR
- NTSC 352x240/CH: MAX. 120fps/4CH & 704x480/CH: MAX. 30fps/4CH
- Record Modes: Manual, Motion, Sensor, and Schedule
- Record Methods: Resolution & Frame Rate
- Triplex Operations: Record, Playback, Network
- Network: Dynamic IP, LAN
- Networking Functions: Live, Search, Playback, Backup, Setup
- Back up via the Network or USB Thumb Drive (Still image & Video Data)
- Input: 110VAC, 60Hz, 1.5A 200VA, Output: +12V 5A
- Power Consumption: 25W Max.
- Humidity: 30%~90%
- Dimensions: 9.6" x 12" x 2.4" / 245W x 304D x 60H mm



Camera Specifications

- 1/3" Sony Super HAD CCD
- Effective Number of Pixels: NTSC=510 H x 492V
- Scanning System: NTSC: 15.734KH
- Sync System: NTSC: 525 Lines (2:1 Interlace)
- Internal Synchronization
- 500 TV Lines
- Sensitivity: IR Off 0.1 Lux / IR on 0 Lux
- S/N Ratio: More Than 50dB
- Gamma Characteristic: 0.45
- Video Output: 1.0Vp-p75ohm
- Electronic Shutter: 1/60sec ~ 1/100,000sec
- 12 VDC Power Supplied from DVR
- Power Consumption: IR On: 350mA Max
- Power Source: Cameras are Powered Through DVR (no additional Cables Needed)
- 4mm Board Lens
- Operation Temperature: +14 to 122 Degrees Farenheit / -10 to +50 Degrees Celsius

